

SEMI-SYNTHETIC SAE 20W-50

API SN/CF, ACEA A3/B4, PETROL & DIESEL OIL

Pennarol 20W-50 Semi-Synthetic is formulated for older vehicles operating under pre emission standards and carburetted power. It is formulated to help provide reliable protection for older, high-mileage engines with the latest technology of cleaning properties to suspend dirt and deposits, anti-wear additives to protect metal surfaces and provide improved fuel economy.

Performance Features

- Protect against oxidation, corrosion and wear.
- Maintains and prolongs the life of your engine
- Provides better high temp wear protection
- Superior protection against viscosity and thermal breakdown
- Keeps engine cool and clean
- Highly recommended for engines operating carburettors
- Removes sludge left behind from inferior oils
- Actively locks away harmful deposits
- Assist in reducing oil leaks and oil consumption

Applications

It is suitable for all petrol and diesel vehicles where **API SN/CF** or earlier specifications are recommended, formulated for use in older style passenger vehicles, light commercials and other large 4 stroke engines, or where high viscosity engine oil is preferred due to harsh operating conditions.

Specifications

- Society of Automotive Engineers (**SAE**) 20W/50
- American Petroleum (**API**) SN/CF
- Association of European Automotive Manufacturers (**ACEA**) A3/B4



PENNAROL OIL COMPANY AUSTRALIA PTY LTD

ABN 97 629 391 715

PO BOX 214, BELFIELD NSW 2191

Phone: 02 9703 5349

www.pennarol.com.au

Email: pennarol@pennaroloils.com.au

SEMI-SYNTHETIC SAE 20W-50

API SN/CF, ACEA A3/B4, PETROL & DIESEL OIL

Manufacturer Specifications

- MB 229.1, 229.3
- FORD WSS-M2C913-A/B/C
- Porsche A40

Typical Data

Test	Result
Viscosity @ 40°C	76.74cSt
Viscosity @ 100°C	11.92cSt
Viscosity Index	151
Specific Gravity	0.852
Product Code- Pack Size	0911. 05/20/205

Note: Pennarol Semi- Synthetic SAE 20W-50 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C

PENNAROL OIL COMPANY AUSTRALIA PTY LTD

ABN 97 629 391 715

PO BOX 214, BELFIELD NSW 2191

Phone: 02 9703 5349

www.pennarol.com.au

Email: pennarol@pennaroloils.com.au