

FULL SYNTHETIC 0W-30 C2

API SN/CF, ACEA A5/B5 PASSENGER CAR PETROL & DIESEL OIL

Pennarol Full Synthetic 0W-30 motor oil is made with a proprietary blend of leading-edge synthetic base stocks. Blended to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits.

Pennarol 0W30 oil helps prolong the life and maintain the efficiency of emission systems in both diesel- and gasoline-powered automobiles. It is formulated to be fully compatible with passenger car diesels that have the latest diesel particulate filters (**DPFs**) and gasoline catalytic converters (**CATs**).

Pennarol 0W-30 meets or exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel- and gasoline-powered passenger car engines.



Performance Features

- Helps reduce particulate build-up in DPFs.
- Helps reduce poisoning of gasoline CATs.
- Helps reduce deposits and sludge build-up to enable long and clean engine life.
- Helps reduce oil aging, allowing extended drain interval protection
- Offers quick cold-weather starting, ultra-fast protection and helps extend engine

FULL SYNTHETIC 0W-30 C2

API SN/CF, ACEA A5/B5 PASSENGER CAR PETROL & DIESEL OIL

Applications

Pennarol 0W-30 is suitable for use in automotive petrol engines including those with hybrid technology where the manufacturer recommends an **API SN, ACEA A5/B5** earlier specification 0W-30 lubricant.

Specifications

- API SN/CF
- ACEA A5/B5
- Ford M2C913 A-D
- STJLR.03.5007
- VW 502.00, 505.00, VW 506.01
- Fiat 9.55535-G1

*Check owners' manual before use.

Typical Data

Test	Result
Viscosity @ 40°C	65.21cSt
Viscosity @ 100°C	12.17cSt
Viscosity Index	179
Specific Gravity	0.851
Product Code- Pack Size	0717/05/20/205

Note: Pennarol Full Synthetic SAE 0W-30 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C