

# FULL SYNTHETIC 0W-40 LONGLIFE

**API SN/CF, ACEA A3/B4 PASSENGER CAR PETROL & DIESEL OIL**

## Description

**Pennarol Full Synthetic 0W-40** motor oil is made with a proprietary blend of leading-edge synthetic base stocks. Blended to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits.

**Pennarol 0W-40** oil helps prolong the life and maintain the efficiency of emission systems in both diesel- and gasoline-powered automobiles.

It is formulated to be fully compatible with passenger car diesels that have the latest diesel particulate filters (**DPFs**) and gasoline catalytic converters (**CATs**).

**Pennarol 0W-40** meets or exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel- and gasoline-powered passenger car engines.

## Performance Features

- Helps reduce particulate build-up in DPFs and reduce poisoning of gasoline CATs.
- Helps reduce deposits and sludge build-up to enable long and clean engine life.
- Helps reduce oil aging, allowing extended drain interval protection.
- Offers quick cold-weather starting, ultra-fast protection and helps extend engine life.

## Applications

**Pennarol 0W-40** is suitable for use in automotive petrol engines including those with hybrid technology where the manufacturer recommends an **API SN/CF, ACEA A3/B4** earlier specification 0W-40 lubricant.



ABN 97 629 391 715  
PO BOX 214, BELFIELD NSW

**PENNAROL OIL COMPANY AUSTRALIA PTY LTD**

ABN 97 629 391 715  
PO BOX 214, BELFIELD NSW 2191  
Phone: 0411-585-621

[www.pennarol.com.au](http://www.pennarol.com.au)

Email: [pennarol@pennarolloils.com.au](mailto:pennarol@pennarolloils.com.au)

# FULL SYNTHETIC 0W-40 LONGLIFE

## API SN/CF PASSENGER CAR PETROL & DIESEL OIL

### Specifications

Pennarol Full Synthetic 0W-40 meets the following performance specifications:

- API SN/CF
- ACEA A3/B4
- Mercedes Benz LL-01, MB 226.5, MB 229.51, 229.31
- BMW-LL-01
- Renault 0700, Renault 0710
- Porsche A40
- VW 502.00, 502.01, VW 505.00

**Note:** Pennarol Full Synthetic SAE 0W-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

### Typical Data

Test	Result
Viscosity @ 40°C	68.21cSt
Viscosity @ 100°C	13.97cSt
Viscosity Index	186
Specific Gravity	0.842
<b>Product Code- Pack Size</b>	<b>0515. /05/20/205</b>

**Note:** Pennarol Full Synthetic SAE 0W-30 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

### Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C