

FULL SYNTHETIC SAE 10W-40

API SN/CF, PASSENGER CAR PETROL & DIESEL OIL

Pennarol 10W-40 Full Synthetic oil that delivers advanced technology for modern engines.

A chemically balanced formula offers maximum engine cleaning properties using special cleansing agents that actively help to suspend harmful dirt and deposits in highly stressed modern engines.

Pennarol 10W-40 unique formulation protects from the moment you start, dramatically reducing engine wear.

Performance Features

- The synthetic technology provides increased protection in high and low temperature applications; -
- Provide continuous protection for all driving conditions, styles and temperatures;
- It delivers superior performance under extreme cold start up conditions compared to thicker grades.

Applications

Pennarol 10W-40 is suitable for

- Use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA **A3/B4**.
- API **SN/CF** or earlier specification 10W40 lubricant.

Specifications

- API SN/CF
- ACEA A3/B4

Manufacturers Specifications

- API SN/CF
- BMW LL-01
- JASO MA
- MB 229.3
- RN 0700/RN0710
- MB 229.5
- VW 501 00
- VW 502 00

*Check owners' manual before use.



FULL SYNTHETIC SAE 10W-40

API SN/CF, PASSENGER CAR PETROL & DIESEL OIL

Typical Data

Test	Result
Viscosity @ 40°C	81.74cSt
Viscosity @ 100°C	12.92cSt
Viscosity Index	169
Specific Gravity	0.85 g/ml
Product Code- Pack Size	0442. 05/20/205

Note: Pennarol Full Synthetic SAE 10W-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C