

# FULL SYNTHETIC SAE 5W-30

**ACEA C3, LONG-LIFE III 504 00/507 00, PASSENGER CAR PETROL & DIESEL OIL**

**Pennarol 5W-30 Long Life III**, is a **Full Synthetic** oil that provides outstanding oil strength for today's engines that work harder, with higher pressures.

**Pennarol 5W-30** has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline powered automobiles.

## Application

- Pennarol 5W-30 **Long Life III** gives the confidence to demand maximum engine performance from VW Group vehicles engineered with variable long drain technology, requiring lower viscosity, stronger oils for longer drain intervals.
- Pennarol Premium 5W-30 Long Life III is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an **ACEA C2-C3** 5W-30 lubricant.
- Pennarol Premium 5W-30 Long Life III is recommended and approved for use in OEM vehicles that require **VW 504 00 / 507 00**, Porsche C30 specifications.

## Performance Features

- Maximises short- and long-term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers complete protection across a variety of engine speeds, conditions, and temperatures
- Sustains maximum performance even when under pressure
- Independently proven to improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures



# FULL SYNTHETIC SAE 5W-30

ACEA C3, LONG-LIFE III 504 00/507 00, PASSENGER CAR PETROL & DIESEL OIL

## Specifications

- ACEA C2-C3
- SAE 5W/30
- API SN/CF

## Manufacturers Specifications

- BMW LL 04
- MB 229.51
- Porsche C30
- VW 504.00 / 507.00

\*Check owners' manual before use.

## Typical Data

Test	Result
Viscosity @ 40°C	68.38 cSt
Viscosity @ 100°C	14.35 cSt
Viscosity Index	174
Specific Gravity	0.852 g/ml
<b>Product Code- Pack Size</b>	<b>0820. 05/20/205</b>

**Note:** Pennarol Full Synthetic SAE 5W-30 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C